

Page: 1 / 15

Revision nr: 10.0

Issue date : 26/08/2022

Supersedes : 02/06/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance

Trade name : PAVING GRADE BITUMEN

EURO BITUMEN 160/220

(HOT STATE)

Chemical name : Asphalt, oxidized

EC-No. : 265-196-4 CAS-No. : 64742-93-4

REACH registration No : 01-2119498270-36-0049

Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, Professional use, Consumer use

Use of the substance/mixture : Coating

Rubber products

Building and construction work

#### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Supplier

NIS a.d. Novi Sad Narodnog Fronta 12 21000 Novi Sad - Serbia

T + 381 (0) 21 481 1111

Dragana.Cvetkov@nis.eu (REACH)

Only Representative

BENS Consulting d.o.o.

Špruha 19

1236 Trzin - Slovenija T +386 41 979 800

info@bens-consulting.eu

## 1.4. Emergency telephone number

Emergency number : + 381 (0) 21 481 1111

Only available during office hours.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified



Page: 2 / 15

Revision nr : 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes: 02/06/2022

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Child-resistant fastening : Not applicable Tactile warning : Not applicable

2.3. Other hazards

Other hazards : Results of PBT and vPvB assessment : Not applicable.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Substance name : PAVING GRADE BITUMEN

EURO BITUMEN 160/220

(HOT STATE)

CAS-No. : 64742-93-4 EC-No. : 265-196-4

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Asphalt, oxidized	(CAS-No.) 64742-93-4 (EC-No.) 265-196-4 (EC Index) -	100	Not classified

Full text of H- and EUH-statements: see section 16

### 3.2. Mixtures

Not applicable

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection!. Concerning personal protective

equipment to use, see section 8. Never give anything by mouth to an

unconscious person. In case of doubt or persistent symptoms, consult always a

physician. Show this safety data sheet to the doctor in attendance.

Inhalation : Remove casualty to fresh air and keep warm and at rest. In case of doubt or

persistent symptoms, consult always a physician.

Skin contact : Remove contaminated clothing and shoes. Gently wash with plenty of soap

and water. In case of doubt or persistent symptoms, consult always a

physician.



Page : 3 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes: 02/06/2022

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. Remove

contact lenses, if present and easy to do. Continue rinsing. In case of doubt or

persistent symptoms, consult always a physician.

Ingestion : Rinse mouth thoroughly with water. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Elevated temperatures or mechanical action may form vapours, mists or fumes

which may be irritating to the eyes, nose, throat and lungs.

Skin contact : Hot product (liquid) can cause thermal burns.

Eyes contact : Hot product (liquid) can cause thermal burns.

Ingestion : According to experience not expected.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray, Alcohol resistant foam, Carbon dioxide, Dry extinguishing

powder. Sand.

Unsuitable extinguishing media : Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards

Hazardous decomposition products in

case of fire

: Combustible.

: Carbon oxides (CO, CO2). Nitrogen oxides (NOx). Sulphur oxides. sulphuric

acid. Hydrogen sulfide.

#### 5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain

the extinguishing fluids by bunding. Prevent fire fighting water from entering

the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-

contained breathing apparatus.

Other information : Do not allow run-off from fire-fighting to enter drains or water courses.

Dispose of waste in accordance with environmental legislation.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation.

Do not breathe dust. Avoid contact with skin, eyes and clothing. Wear

recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is

adequately earthed.

#### 6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal

are in place. Concerning personal protective equipment to use, see section 8.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.



Page : 4 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes: 02/06/2022

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leak if safe to do so. Dam up the solid spill. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Large spills: scoop solid spill into closing containers. This material and its container must be disposed of in a safe way, and as per local legislation. After cleaning, flush traces away with water.

#### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Do not exceed maximum handling and storage temperatures. The current recommended maximum temperatures for bitumen Air-Rectified bitumen are 200°C and for Severely Oxidised bitumen 230°C, respectively. Use above these temperatures is advised against. Provide adequate ventilation. Do not breathe dust. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment.

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10.

Heat and ignition sources

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Special rules on packaging

: Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep container tight closed.

Packaging materials

: Keep only in the original container. Suitable material: Steel. Stainless steel. Coated steels. metal containers. Unsuitable material: Synthetic material.

### 7.3. Specific end use(s)

Coating. Rubber products. Building and construction work.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Asphalt, oxidized (64742-93-4)		
Germany	Occupational exposure limit value (mg/m³) (TRGS900)	1,5 mg/m³ (Steam and aerosol in the hot processing of distillation and air-rectified bitumen)

Asphalt, oxidized (64742-93-4)	
DNEL/DMEL (workers)	
Long-term - local effects, inhalation	(8h) 2,9 mg/m <sup>3</sup>



Page : 5 / 15

Revision nr: 10.0

Issue date : 26/08/2022

MEN Supersedes : 02/06/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Asphalt, oxidized (64742-93-4)

DNEL/DMEL (general population)

Long-term - local effects, inhalation (24h) 0,6 mg/m³

PNEC (additional information)

Additional information No data available UVCB

Additional information

: Occupational Exposure Limits :. No data available. Recommended monitoring

procedures:. Personal air monitoring. Room air monitoring

8.2. Exposure controls

Engineering measure(s) : Provide adequate ventilation. Use only in area provided with appropriate

exhaust ventilation. Ensure equipment is adequately earthed. Organisational measures to prevent /limit releases, dispersion and exposure. See Section 7 for

information on safe handling.

Personal protective equipment : The type of protective equipment must be selected according to the

concentration and amount of the dangerous substance at the specific

workplace.

Hand protection : The selection of specific gloves for a specific application and time of use in a

working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and

the instructions/specification of the supplier of gloves. (EN407)

Eye protection : During splash contact: Use suitable eye protection (EN166): face shield

Body protection : Wear suitable protective clothing. Overalls, apron and boots recommended.

Respiratory protection : Not required for normal conditions of use. In the case of vapour formation use

a respirator with an approved filter. Self-contained open-circuit compressed air

breathing apparatus (EN 137)

Thermal hazard protection : Heat resistant gloves (EN407).

Environmental exposure controls : Do not allow to enter into surface water or drains. Comply with applicable

Community environmental protection legislation. Avoid release to the

environment.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid Appearance : Solid.

Colour : dark brown -. Black.

Odour : No data available.

Odour threshold : No data available

pH : Not applicable

pH solution : Not available

Relative evaporation rate (butylacetate=1) : No data available

Melting / freezing point : 30 – 128 °C (ASTM D36)

Freezing point : No data available

Initial boiling point and boiling range : > 320 °C

Flash point :  $\geq$  220 °C (ASTM D92 / EN ISO 2592)

Auto-ignition temperature : > 400 °C

Decomposition temperature : No data available



Page : 6 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes : 02/06/2022

Flammability : Non flammable

Vapour pressure : << 0,1 kPa (20°C)

Vapour density : No data available

Relative density : 0,925 – 1,07 (15 °C)

Solubility : Water: Substance is complex UVCB.

Partition coefficient n-octanol/water : Substance is complex UVCB.

Kinematic viscosity : 1000 - 16000 mm<sup>2</sup>/s (60°C)(EN12595)

>= 100 mm<sup>2</sup>/s (100°C)(EN12595) >= 135 mm<sup>2</sup>/s (135°C)(EN12595)

Dynamic viscosity : No data available

Explosive properties : Not applicable. The study does not need to be conducted because there are

no chemical groups associated with explosive properties present in the

molecule.

Oxidising properties : Not applicable. The classification procedure needs not to be applied because

there are no chemical groups present in the molecule which are associated

with oxidising properties.

Explosive limits : No data available

Particle size : Not available Particle size distribution : Not available Particle shape : Not available : Not available Particle aspect ratio Particle aggregation state : Not available Particle agglomeration state : Not available Particle specific surface area : Not available Particle dustiness : Not available

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Additional information : Softening point 35 - 43 °C (EN 1427)

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

Combustible. Reference to other sections: 10.4 & 10.5.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

None under normal processing.

## 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.



Page : 7 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes: 02/06/2022

#### 10.5. Incompatible materials

Incompatible with strong acids and oxidizing agents. Bases. Nitrates . See Section 7 for information on safe handling.

### 10.6. Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. Reference to other sections 5.2.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Asphalt, oxidized (64742-93-4)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg
LC50/inhalation/4h/rat	94,4 mg/m <sup>3</sup>
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Serious eye damage/irritation	<ul> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>pH: Not applicable</li> </ul>
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
	NOAEC, Inhalation, Rat: 300 mg/m <sup>3</sup>
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

Asphalt, oxidized (64742-93-4)	
NOAEL, subacute, Dermal, rabbit, local	200 mg/kg bw/day
NOAEL, subacute, Dermal, rabbit, systemic	2000 mg/kg bw/day
NOAEC, subchronic, Inhalation, Rat, systemic	103.9 mg/m <sup>3</sup>
NOAEC, subchronic, Inhalation, Rat, local	10.4 mg/m <sup>3</sup>

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE) (64742-93-4)	
Kinematic viscosity	1000 - 16000 mm <sup>2</sup> /s (60°C)(EN12595) >= 100 mm <sup>2</sup> /s (100°C)(EN12595) >= 135 mm <sup>2</sup> /s (135°C)(EN12595)

Other information

: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.



Page : 8 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes : 02/06/2022

### 11.2. Information on other hazards

## 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2 Other information

Other information

: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Environmental properties : Ecological injuries are not known or expected under normal use.

Hazardous to the aquatic environment,

short-term (acute)

: Not classified

Hazardous to the aquatic environment,

long-term (chronic)

: Not classified

Asphalt, oxidized (64742-93-4)		
EC50 72h - Algae [1]	56 mg/l (Species: Pseudokirchneriella subcapitata)	
Acute (short-term) fish toxicity, LL50 (96h)	> 1000 mg/l QSAR	
Chronic (long-term) fish toxicity, LL50 (28d)	> 1000 mg/l QSAR	
Chronic (long-term) fish toxicity, NOEL	≥ 1000 mg/l QSAR	
Acute (short-term) daphnia toxicity, LL50 (48h)	> 1000 mg/l QSAR	
Chronic (long-term) daphnia toxicity, NOEL (21d)	≥ 1000 mg/l QSAR	
Acute (short-term) algae toxicity, EL50 (72h)	> 1000 mg/l QSAR (Inhibition of growth rate.)	
Toxicity to other organisms (Tetrahymena pyriformis), LL50 (40h)	> 1000 mg/l QSAR	
Toxicity to other organisms (Tetrahymena Pyriformis), NOEL (40h)	> 1000 mg/l Inhibition of growth rate.	

### 12.2. Persistence and degradability

PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE) (64742-93-4)	
Persistence and degradability	No additional information available.



Page : 9 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes: 02/06/2022

#### 12.3. Bioaccumulative potential

PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE) (64742-93-4)	
Partition coefficient n-octanol/water	Substance is complex UVCB.
Bioaccumulative potential	No additional information available.

#### 12.4. Mobility in soil

PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE) (64742-93-4)	
Mobility in soil	No data available
Ecology - soil	No data available.

Asphalt, oxidized (64742-93-4)	
Surface tension	Not applicable

#### 12.5. Results of PBT and vPvB assessment

## PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE) (64742-93-4)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

### 12.7. Other adverse effects

Other adverse effects : No data available

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.



Page: 10 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes : 02/06/2022

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)

: This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

The following Waste Codes are only suggestions: 05 01 17 - bitumen .

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID		
14.1. UN number						
3257 3257 3257 3257		3257	3257			
14.2. UN proper ship	14.2. UN proper shipping name					
ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ()) Transport document de		Elevated temperature liquid, n.o.s. (Asphalt, oxidized ())	ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ())	ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ())		
UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ()), 9, III, (D)	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ()), 9, III	UN 3257 Elevated temperature liquid, n.o.s. (Asphalt, oxidized ()), 9	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ()), 9, III	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized ()), 9, III		
14.3. Transport haza	rd class(es)					
9	9	9	9	9		
	•	Not applicable				
	14.4. Packing group					
III	III	Not applicable	III	III		
Dangerous for the environment: No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No		
Silvironinione . No	Marine pollutant : No	on vii on in one . 140	Silvinoillione . NO	Silvinoillione . 140		
No supplementary information available						

# 14.6. Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) : M9

Special provisions : 274, 643, 668

Limited quantities (ADR) : 0

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P099, IBC99

Portable tank and bulk container

instructions (ADR)

: T3

Portable tank and bulk container

special provisions (ADR)

: TP3, TP29



Page: 11 / 15

Revision nr: 10.0

Issue date: 26/08/2022

Supersedes: 02/06/2022

# PAVING GRADE BITUMEN **EURO BITUMEN 160/220** (HOT STATE)

Tank code (ADR) **LGAV** 

TU35, TC7, TE6, TE14, TE18, TE24 Tank special provisions (ADR)

Vehicle for tank carriage AT Transport category (ADR) 3 VC3 Special provisions for carriage - Bulk

(ADR)

Hazard identification number (Kemler:

No.)

Orange plates

99

Tunnel restriction code EAC code 2Y

- Transport by sea

: 232, 274 Special provisions (IMDG)

: 0 Limited quantities (IMDG) Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P099 IBC packing instructions (IMDG) : IBC01 Tank instructions (IMDG) : T3

Tank special provisions (IMDG) : TP3, TP29 : F-A EmS-No. (Fire) : S-P EmS-No. (Spillage) : A Stowage category (IMDG) Stowage and handling (IMDG) : SW5

Flash point (IMDG) : above 100°C

Properties and observations (IMDG) : Any liquid which is transported at or above 100°C but below its flashpoint. May

cause fire if in contact with combustible material due to extreme temperature.

- Air transport

: E0 PCA Excepted quantities (IATA)

PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity : Forbidden

(IATA)

PCA packing instructions (IATA) : Forbidden PCA max net quantity (IATA) : Forbidden CAO packing instructions (IATA) : Forbidden CAO max net quantity (IATA) : Forbidden

ERG code (IATA) : 9L

- Inland waterway transport

Classification code (ADN) : M9

Special provisions (ADN) : 274, 643, 668

Limited quantities (ADN) : 0 Excepted quantities (ADN) : E0 : T Carriage permitted (ADN)



Page: 12 / 15

Revision nr: 10.0

Issue date: 26/08/2022

Supersedes: 02/06/2022

# PAVING GRADE BITUMEN **EURO BITUMEN 160/220** (HOT STATE)

: PP Equipment required (ADN) Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : M9

Special provisions (RID) : 274, 643, 668

Limited quantities (RID) : 0 Excepted quantities (RID) : E0

Packing instructions (RID) : P099, IBC99

Portable tank and bulk container

instructions (RID)

: T3

Portable tank and bulk container special: TP3, TP29

provisions (RID)

Tank codes for RID tanks (RID) : LGAV

Special provisions for RID tanks (RID) : TU35, TE6, TE14

Transport category (RID) : 3 Special provisions for carriage - Bulk : VC3

: CW17, CW31

Loading, unloading and handling (RID)

Special provisions for carriage -

Hazard identification number (RID) : 99

#### 14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.

### **SECTION 15: Regulatory information**

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

No REACH Annex XVII restrictions **PAVING GRADE BITUMEN** EURO BITUMEN 160/220 (HOT STATE) is not on the REACH Candidate List **PAVING GRADE BITUMEN** EURO BITUMEN 160/220

(HOT STATE) is not on the REACH Annex XIV List

#### 15.1.2. National regulations

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory



Page: 13 / 15

Revision nr: 10.0

Issue date : 26/08/2022

Supersedes : 02/06/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

#### **France**

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
na	Not Applicable	na	na

#### Germany

Regulatory reference : Not classified according to Regulation Governing Systems for Handling

Substances Hazardous to Waters (AwSV)

Hazardous Incident Ordinance (12.

BImSchV)

: Is not subject of the 12. BlmSchV (Hazardous Incident Ordinance)

#### Netherlands

Waterbezwaarlijkheid : B (4) - Weinig schadelijk voor in het water levende organismen

SZW-lijst van kankerverwekkende

stoffen

: The substance is not listed

SZW-lijst van mutagene stoffen
SZW-lijst van reprotoxische stoffen –

Borstvoeding

: The substance is not listed: The substance is not listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

: The substance is not listed

SZW-lijst van reprotoxische stoffen -

Ontwikkeling

: The substance is not listed

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out

## **SECTION 16: Other information**

### Indication of changes:

2.3	ED text	Added
4.3	Indication of any immediate medical attention and special treatment needed	Added
7.1	Precautions for safe handling	Added
7.3	Specific end use(s)	Added
9.2	Information with regard to physical hazard classes	Added
9.2	Other safety characteristics	Added
11.2	Adverse health effects caused by endocrine disrupting properties	Added
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added
14.7	Maritime transport in bulk according to IMO	Added



Page: 14/15

Revision nr: 10.0

Issue date: 26/08/2022

Supersedes: 02/06/2022

# **PAVING GRADE BITUMEN EURO BITUMEN 160/220** (HOT STATE)

	instruments		
15	REACH Annex XVII	Added	
15.1	Installations classées	Added	
15.1	Waterbezwaarlijkheid	Added	
16	Training advice	Added	

#### Abbreviations and acronyms:

Appleviation	ns and actoryths.
	DNEL = Derived No Effect Level
	DMEL = Derived Minimal Effect level
	PNEC = Predicted No Effect Concentration
	OEL-STEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	TWA = time weighted average
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	NOEL = no-observed-effect level
	NOEC = No observed effect concentration
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	EWC = European waste catalogue
	NA = Not applicable
	N.O.S. = Not Otherwise Specified
	VOC = Volatile organic compounds
	mg/kg BW = mg/kg bodyweight
	QSAR = Quantitative structure-activity relationship (QSAR)
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin  ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC  IATA = International Air Transport Association  IMDG = International Maritime Dangerous Goods Code  LEL = Lower Explosive Limit/Lower Explosion Limit  UEL = Upper Explosion Limit/Upper Explosive Limit  REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals  WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)  ABM = Algemene beoordelingsmethodiek  BTT = Breakthrough time (maximum wearing time)
	NOEL: no-observed-effect level
	STOT = Specific Target Organ Toxicity

Sources of key data used to compile the : European Chemicals Bureau, CSR. Safety Data Sheet: Supplier.

datasheet

Training advice

: Training staff on good practice. Manipulations are to be done only by qualified

and authorised persons.

Other information : Classification - Assessment method: CLP Calculation method (Article 9).

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Classification according to Regulation (EC) No. 1272/2008 [CLP] Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Page: 15 / 15

Revision nr: 10.0

Issue date : 26/08/2022

# PAVING GRADE BITUMEN EURO BITUMEN 160/220 (HOT STATE)

Supersedes : 02/06/2022

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.