	SAFETY DATA SHEET	Page : 1 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : POLYMER MODIFIED BITUMEN
45/80-65
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Distribution
Intermediate
Formulation
Lubricants,
Coating,
Rubber products
Road and construction applications
Drilling applications
Fuels

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

NIS a.d. Novi Sad
Narodnog Fronta 12
21000 Novi Sad - Serbia
T + 381 (0) 21 481 1111
Dragana.Cvetkov@nis.eu (REACH)

Only Representative

BENS Consulting d.o.o.
Špruha 19
1236 Trzin - Slovenija
T +386 41 979 800
info@bens-consulting.eu

1.4. Emergency telephone number

Emergency number : + 381 (0) 21 481 1111
Only available during office hours.


Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

	SAFETY DATA SHEET	Page : 2 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Not applicable.

2.3. Other hazards

Other hazards : PBT/vPvB data. This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB). This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Asphalt, oxidized	(CAS-No.) 64742-93-4 (EC-No.) 265-196-4 (REACH-no) 01-2119498270-36-0049	95 – 100	Not classified
SBS Polymer (Styrene-butadiene-styrene)	(CAS-No.) 9003-55-8 (EC-No.) 618-370-2	≤ 5	Not classified


SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection!. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.
Inhalation	: Remove casualty to fresh air and keep warm and at rest. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Remove contaminated clothing and shoes. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth thoroughly with water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: Elevated temperatures or mechanical action may form vapours, mists or fumes which may be irritating to the eyes, nose, throat and lungs.
Skin contact	: Hot product (liquid) can cause thermal burns.
Eyes contact	: Hot product (liquid) can cause thermal burns.
Ingestion	: Ingestion is not considered a potential route of exposure.

	SAFETY DATA SHEET	Page : 3 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂), powder, alcohol-resistant foam, water spray.
 Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Not flammable. Heating will cause a rise in pressure with a risk of bursting.
 Hazardous decomposition products in case of fire : Carbon oxides (CO, CO₂), nitrogen oxides (NO_x) and sulphur oxides.

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
 Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
 Other information : Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel : Keep upwind. Provide adequate ventilation. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Evacuate unnecessary personnel.

6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions


Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Dispose of contaminated materials in accordance with current regulations. Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation. After cleaning, flush traces away with water.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8 . Concerning disposal elimination after cleaning, see section 13.

	SAFETY DATA SHEET	Page : 4 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment.

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage.

Heat and ignition sources

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Special rules on packaging

: Containers which are opened should be properly resealed and kept upright to prevent leakage.

Packaging materials

: Keep only in the original container. Suitable material: Mild steel, Stainless steel. Unsuitable material: Synthetic material.

7.3. Specific end use(s)

For further information see section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Asphalt, oxidized (64742-93-4)		
Germany	Occupational exposure limit value (mg/m ³) (TRGS900)	1,5 mg/m ³ (Steam and aerosol in the hot processing of distillation and air-rectified bitumen)

Asphalt, oxidized (64742-93-4)	
DNEL/DMEL (workers)	
Long-term - local effects, inhalation	2,88 mg/m ³
DNEL/DMEL (general population)	
Long-term - local effects, inhalation	0,61 mg/m ³
PNEC (additional information)	
Additional information	No data available UVCB

Additional information

: Asphalt, oxidized (CAS 64742-93-4): Concentration measurement in air. Personal air monitoring


8.2. Exposure controls

Engineering measure(s)

: Provide adequate ventilation. Use only in area provided with appropriate exhaust ventilation. Ensure equipment is adequately earthed. Organisational measures to prevent /limit releases, dispersion and exposure. See Section 7 for information on safe handling.

Personal protective equipment

: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.


	SAFETY DATA SHEET	Page : 5 / 14
		Revision nr : 8.0
		Issue date : 31/08/2022
	POLYMER MODIFIED BITUMEN 45/80-65	Supersedes : 22/03/2016

Hand protection	: The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves. (EN407)
Eye protection	: During splash contact: Use suitable eye protection (EN166): face shield. tightly fitting safety goggles
Body protection	: Wear suitable protective clothing. Overalls, apron and boots recommended.
Respiratory protection	: In the case of vapour formation use a respirator with an approved filter. Self-contained open-circuit compressed air breathing apparatus (EN 137). Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: A/P2. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Use dedicated equipment. Heat resistant gloves (EN407).
Environmental exposure controls	: Do not allow to enter into surface water or drains. Comply with applicable Community environmental protection legislation. Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: viscous liquid. / Solid <= 19 °C. Liquid.
Colour	: dark brown. Black.
Odour	: Characteristic.
Odour threshold	: No data available No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting / freezing point	: 30 – 128 °C (ASTM D36)
Freezing point	: No data available
Softening point	: ≥ 65 °C
Initial boiling point and boiling range	: > 320 °C
Flash point	: ≥ 250 °C (EN ISO 2592)
Auto-ignition temperature	: > 400 °C
Decomposition temperature	: No data available
Flammability	: Not applicable,liquid
Vapour pressure	: << 0,1 kPa (20°C)
Vapour density	: No data available
Relative density	: 0,925 – 1,07 g/cm ³ (15°C)
Solubility	: Water: insoluble (20°C)
Partition coefficient n-octanol/water	: No data available
Kinematic viscosity	: 1000 - 16000 mm ² /s (60°C)(EN12595) 1189 - 8650 mPa.s (100°C)(EN13302) 80 - 3210 mm ² /s (135°C)(EN12595)
Dynamic viscosity	: No data available
Explosive properties	: Not applicable. The study does not need to be conducted because there are no chemical groups associated with explosive properties present in the molecule.

	SAFETY DATA SHEET	Page : 6 / 14
		Revision nr : 8.0
		Issue date : 31/08/2022
	POLYMER MODIFIED BITUMEN 45/80-65	Supersedes : 22/03/2016

Oxidising properties	: Not applicable. The classification procedure needs not to be applied because there are no chemical groups present in the molecule which are associated with oxidising properties.
Explosive limits	: No data available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : penetration (25°C) 45-80

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. See Section 7 for information on safe handling.

10.5. Incompatible materials

Incompatible with strong acids and oxidizing agents. Bases . See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Reference to other sections 5.2.


SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Not classified (Based on available data, the classification criteria are not met)

Asphalt, oxidized (64742-93-4)	
LD50/oral/rat	> 5000 mg/kg
LD50/dermal/rabbit	> 2000 mg/kg
LC50/inhalation/4h/rat	94,4 mg/m ³

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
pH: No data available

	SAFETY DATA SHEET	Page : 7 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: No data available
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

Asphalt, oxidized (64742-93-4)	
NOAEL, subacute, Dermal, rabbit, local	200 mg/kg bw/day
NOAEL, subacute, Dermal, rabbit, systemic	2000 mg/kg bw/day
NOAEC, subchronic, Inhalation, Rat, systemic	103.9 mg/m ³
NOAEC, subchronic, Inhalation, Rat, local	10.4 mg/m ³

Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
-------------------	---

POLYMER MODIFIED BITUMEN 45/80-65	
Kinematic viscosity	1000 - 16000 mm ² /s (60°C)(EN12595) 1189 - 8650 mPa.s (100°C)(EN13302) 80 - 3210 mm ² /s (135°C)(EN12595)

Other information	: Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.
-------------------	--

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
--	--

11.2.2 Other information

Other information	: Symptoms related to the physical, chemical and toxicological characteristics, For further information see section 4
-------------------	---

SECTION 12: Ecological information


12.1. Toxicity

Environmental properties	: Not hazardous.
--------------------------	------------------

Hazardous to the aquatic environment, short-term (acute)	: Not classified
--	------------------

Hazardous to the aquatic environment, long-term (chronic)	: Not classified
---	------------------

Asphalt, oxidized (64742-93-4)	
EC50 72h - Algae [1]	56 mg/l (Species: Pseudokirchneriella subcapitata)
Acute (short-term) fish toxicity, LL50 (96h)	> 1000 mg/l QSAR
Chronic (long-term) fish toxicity, LL50 (28d)	> 1000 mg/l QSAR

	SAFETY DATA SHEET	Page : 8 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

Chronic (long-term) fish toxicity, NOEL	≥ 1000 mg/l QSAR
Acute (short-term) daphnia toxicity, LL50 (48h)	> 1000 mg/l QSAR
Chronic (long-term) daphnia toxicity, NOEL (21d)	≥ 1000 mg/l QSAR
Acute (short-term) algae toxicity, EL50 (72h)	> 1000 mg/l QSAR (Inhibition of growth rate.)
Toxicity to other organisms (Tetrahymena pyriformis), LL50 (40h)	> 1000 mg/l QSAR
Toxicity to other organisms (Tetrahymena Pyriformis), NOEL (40h)	> 1000 mg/l Inhibition of growth rate.

12.2. Persistence and degradability

POLYMER MODIFIED BITUMEN 45/80-65	
Persistence and degradability	Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

12.3. Bioaccumulative potential

POLYMER MODIFIED BITUMEN 45/80-65	
Partition coefficient n-octanol/water	No data available
Bioaccumulative potential	No additional information available.

12.4. Mobility in soil

POLYMER MODIFIED BITUMEN 45/80-65	
Mobility in soil	No data available
Ecology - soil	No data available.

Asphalt, oxidized (64742-93-4)

Surface tension	Not applicable
-----------------	----------------

12.5. Results of PBT and vPvB assessment

POLYMER MODIFIED BITUMEN 45/80-65	
Results of PBT assessment	This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Endocrine disrupting properties


Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Other adverse effects

: No data available

	SAFETY DATA SHEET	Page : 9 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

SECTION 13: Disposal considerations





13.1. Waste treatment methods

Product/Packaging disposal recommendations : Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities
The following Waste Codes are only suggestions:
05 01 17 - bitumen .


SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN


ADR	IMDG	IATA	ADN	RID
14.1. UN number				
3257	3257	3257	3257	3257
14.2. UN proper shipping name				
ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I))	ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I))	Elevated temperature liquid, n.o.s. (Asphalt, oxidized (I))	ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I))	ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I))
Transport document description				
UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I)), 9, III, (D)	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I)), 9, III	UN 3257 Elevated temperature liquid, n.o.s. (Asphalt, oxidized (I)), 9	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I)), 9, III	UN 3257 ELEVATED TEMPERATURE LIQUID, N.O.S. (Asphalt, oxidized (I)), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
		Not applicable		
14.4. Packing group				
III	III	Not applicable	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

14.6. Special precautions for user

Special precautions for user : Polymer modified bitumen is dispatched and transported the car tanks. Tanks that are used to transport polymer modified bitumen must be satisfactory purity. It is preferred that therein the previously transported to a polymer modified bitumen. Tanks which previously transported travel bitumen, fuel oil, etc. can not be used to transport polymer modified bitumen without rinsing to remove traces of these products . Minimum temperature polymer modified bitumen when loading the tanks should be 165 °C.

	SAFETY DATA SHEET	Page : 10 / 14
		Revision nr : 8.0
		Issue date : 31/08/2022
	POLYMER MODIFIED BITUMEN 45/80-65	Supersedes : 22/03/2016

- Overland transport

Classification code (ADR)	: M9
Special provisions	: 274, 643, 668
Limited quantities (ADR)	: 0
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P099, IBC99
Portable tank and bulk container instructions (ADR)	: T3
Portable tank and bulk container special provisions (ADR)	: TP3, TP29
Tank code (ADR)	: LGAV
Tank special provisions (ADR)	: TU35, TC7, TE6, TE14, TE18, TE24
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Bulk (ADR)	: VC3
Hazard identification number (Kemler No.)	: 99
Orange plates	: 


Tunnel restriction code	: D
EAC code	: 2Y

- Transport by sea

Special provisions (IMDG)	: 232, 274
Limited quantities (IMDG)	: 0
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P099
IBC packing instructions (IMDG)	: IBC01
Tank instructions (IMDG)	: T3
Tank special provisions (IMDG)	: TP3, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-P
Stowage category (IMDG)	: A
Stowage and handling (IMDG)	: SW5
Flash point (IMDG)	: above 100°C
Properties and observations (IMDG)	: Any liquid which is transported at or above 100°C but below its flashpoint. May cause fire if in contact with combustible material due to extreme temperature.

- Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: Forbidden
PCA max net quantity (IATA)	: Forbidden
CAO packing instructions (IATA)	: Forbidden
CAO max net quantity (IATA)	: Forbidden
ERG code (IATA)	: 9L

	SAFETY DATA SHEET	Page : 11 / 14
		Revision nr : 8.0
		Issue date : 31/08/2022
	POLYMER MODIFIED BITUMEN 45/80-65	Supersedes : 22/03/2016

- Inland waterway transport

Classification code (ADN)	: M9
Special provisions (ADN)	: 274, 643, 668
Limited quantities (ADN)	: 0
Excepted quantities (ADN)	: E0
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

- Rail transport

Classification code (RID)	: M9
Special provisions (RID)	: 274, 643, 668
Limited quantities (RID)	: 0
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P099, IBC99
Portable tank and bulk container instructions (RID)	: T3
Portable tank and bulk container special provisions (RID)	: TP3, TP29
Tank codes for RID tanks (RID)	: LGAV
Special provisions for RID tanks (RID)	: TU35, TE6, TE14
Transport category (RID)	: 3
Special provisions for carriage – Bulk (RID)	: VC3
Special provisions for carriage - Loading, unloading and handling (RID)	: CW17, CW31
Hazard identification number (RID)	: 99

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC	: No data available.
-----------	----------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations


Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list
Contains no REACH Annex XIV substances

15.1.2. National regulations

France

No ICPE	Installations classées Désignation de la rubrique	Code Régime	Rayon
na	Not Applicable	na	na

Germany

	SAFETY DATA SHEET	Page : 12 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

Regulatory reference : WGK nwg, Non-hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

Waterbezwaarlijkheid : B (4) - Weinig schadelijk voor in het water levende organismen
SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

15.2. Chemical safety assessment


Not applicable

For the following substances of this mixture a chemical safety assessment has been carried out
Asphalt, oxidized

SECTION 16: Other information

Indication of changes:

2.3	ED text	Added	
4.3	Indication of any immediate medical attention and special treatment needed	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Added	
5.3	Other information	Added	
7.1	Precautions for safe handling	Added	
7.2	Packaging materials	Added	
7.2	Special rules on packaging	Added	
7.2	Heat and ignition sources	Added	
9.2	Information with regard to physical hazard classes	Added	
9.2	Other safety characteristics	Added	
11.2	Adverse health effects caused by endocrine disrupting properties	Added	
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added	
14.7	Maritime transport in bulk according to IMO instruments	Added	
15.1	Installations classées	Added	

	SAFETY DATA SHEET	Page : 13 / 14
		Revision nr : 8.0
	POLYMER MODIFIED BITUMEN 45/80-65	Issue date : 31/08/2022
		Supersedes : 22/03/2016

15.1	Water hazard class (WGK)	Modified	
15.1	Waterbezwaarlijkheid	Added	

Abbreviations and acronyms:


	DNEL = Derived No Effect Level
	DMEL = Derived Minimal Effect level
	PNEC = Predicted No Effect Concentration
	OEL-STEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	TWA = time weighted average
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	NOEL = no-observed-effect level
	NOEC = No observed effect concentration
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	EWG = European waste catalogue
	NA = Not applicable
	N.O.S. = Not Otherwise Specified
	VOC = Volatile organic compounds
	mg/kg BW = mg/kg bodyweight
	QSAR = Quantitative structure-activity relationship (QSAR)
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)
	ABM = Algemene beoordelingsmethodiek
	BTT = Breakthrough time (maximum wearing time)
	NOEL: no-observed-effect level
	STOT = Specific Target Organ Toxicity

Sources of key data used to compile the datasheet : European Chemicals Bureau : ecb.jrc.it CSR, SDS supplier.

Training advice : Training staff on good practice.

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

	SAFETY DATA SHEET	Page : 14 / 14
		Revision nr : 8.0
		Issue date : 31/08/2022
	POLYMER MODIFIED BITUMEN 45/80-65	Supersedes : 22/03/2016