

Page: 1 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes: 17/08/2022

FUELS, DIESEL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name/designation : FUELS, DIESEL
EC Index : 649-224-00-6
EC-No. : 269-822-7
CAS-No. : 68334-30-5

REACH registration No. : 01-2119484664-27-0186

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial uses, Professional use

Use of the substance/mixture : Fuels

Further information: see exposure scenarios attached to this safety data

sheet.

Title	Use descriptors
Use as an intermediate	SU8, SU9, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9,
(ES Ref.: 01b)	PROC15, PROC28, ERC6a, ESVOC SPERC 6.1a.v1
Distribution of substance	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15,
(ES Ref.: 01a)	ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SPERC 1.1b.v1
Use in oil and gas field drilling and	PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC28,
production operations	ERC4, QUALITATIVE ASSESSMENT FOR ENVIRONMENT
(ES Ref.: 07)	
Use in functional fluids	PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC9, PROC28, ERC7, ESVOC
(ES Ref.: 13a)	SPERC 7.13a.v1
Use as a fuel	PROC1, PROC2, PROC8a, PROC8b, PROC16, PROC28, ERC7, ESVOC
(ES Ref.: 12a)	SPERC 7.12a.v1
Use as a fuel	PROC1, PROC2, PROC8a, PROC8b, PROC16, PROC28, ERC9a, ERC9b,
(ES Ref.: 12b)	ESVOC SPERC 9.12b.v1
Use as a fuel	PC13, ERC9a, ERC9b, ESVOC SPERC 9.12c.v1
(ES Ref.: 12c)	
Formulation & (re)packing of substances	PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9,
and mixtures	PROC14, PROC15, PROC28, ERC2, ESVOC SPERC 2.2.v1
(ES Ref.: 02)	

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

NIS a.d. Novi Sad Narodnog Fronta 12 21000 Novi Sad Serbia

T + 381 (0) 21 481 1111 REACHNIS@nis.rs Only Representative

BENS Consulting d.o.o.

Špruha 19 1236 Trzin Slovenija

T +386 41 979 800

info@bens-consulting.eu



Page: 2 / 22

Revision nr: 13.0

Issue date: 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Emergency telephone number

Emergency number + 381 (0) 21 481 1111

Only available during office hours.

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3	H226
Acute toxicity (inhal.), Category 4	
Skin corrosion/irritation, Category 2	
Carcinogenicity, Category 2	
Specific target organ toxicity – Repeated exposure,	
Category 2	
Aspiration hazard, Category 1	
Hazardous to the aquatic environment – Chronic	

Hazard, Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









GHS02

GHS08

GHS09

Signal word

: Danger

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation. H332 - Harmful if inhaled.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated

exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. P260 - Do not breathe vapours.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, eye protection, face



Page: 3 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

protection.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER, a

doctor. Do NOT induce vomiting.

P391 - Collect spillage.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents and container to an approved waste disposal

plant.

Listed on CLP Annex VI : EC Index-No.: 649-224-00-6

2.3. Other hazards

Other hazards

: Vapours can form explosive mixtures with air. Results of PBT and vPvB assessment: Not applicable. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

 Substance name
 : FUELS, DIESEL

 CAS-No.
 : 68334-30-5

 EC-No.
 : 269-822-7

 EC Index
 : 649-224-00-6

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fuels, diesel	CAS-No.: 68334-30-5 EC-No.: 269-822-7 EC Index: 649-224-00-6 REACH-no: 01-2119484664- 27-0186	< 100	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

3.2. Mixtures

Not applicable



Page: 4/22

Revision nr: 13.0

Issue date: 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

SECTION 4: First aid measures

4.1. Description of first aid measures

Additional advice : First aider: Pay attention to self-protection!. Concerning personal protective

> equipment to use, see section 8. Never give anything by mouth to an unconscious person. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance.

Inhalation : Remove casualty to fresh air and keep warm and at rest. In case of doubt or

persistent symptoms, consult always a physician.

Skin contact : Remove contaminated clothing and shoes. Gently wash with plenty of soap

and water. In case of doubt or persistent symptoms, consult always a

physician.

Eyes contact : Rinse immediately carefully and thoroughly with eye-bath or water. Remove

contact lenses, if present and easy to do. Continue rinsing. In case of doubt

or persistent symptoms, consult always a physician.

: Rinse mouth thoroughly with water. Do NOT induce vomiting. Get Ingestion

immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation : Harmful if inhaled. May cause respiratory irritation. The following symptoms

may occur: Headache. Nausea. Dizziness. Inhalation of high vapour

concentrations can cause CNS-depression and narcosis.

Skin contact Causes skin irritation.

Eyes contact : Contact with eyes may cause irritation.

Ingestion : May be fatal if swallowed and enters airways. May cause gastrointestinal

irritation, nausea, vomiting and diarrhoea.

Chronic symptoms : May cause damage to organs through prolonged or repeated exposure.

Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Flammable liquid and vapour. Heating will cause a rise in pressure with a

> risk of bursting. Vapours may form explosive mixture with air. Vapours are heavier than air and may travel considerable distance to an ignition source

and flash back to source of vapours.

of fire

Hazardous decomposition products in case : Carbon oxides (CO, CO2). Sulphur oxides. Hydrogen sulfide. Sulfuric acid.

5.3. Advice for firefighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers.

Contain the extinguishing fluids by bunding. Prevent fire fighting water from

entering the environment.



Page: 5 / 22

Revision nr: 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-

contained breathing apparatus.

Other information

: Do not allow run-off from fire-fighting to enter drains or water courses. Dispose of waste in accordance with environmental legislation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

For non-emergency personnel

: Evacuate unnecessary personnel. Keep upwind. Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment. Concerning personal protective equipment to use, see section 8. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure equipment is adequately earthed. Use explosion-proof equipment. Use only non-sparking tools. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.

6.1.2. For emergency responders

For emergency responders

: Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Stop leak if safe to do so. Dam up the liquid spill. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Recover large spills by pumping (use an explosion proof or hand pump). Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). This material and its container must be disposed of in a safe way, and as per local legislation. Cover the spilled liquid product with foam to slow down evaporation. After cleaning, flush traces away with water.

6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.



Page: 6 / 22

Revision nr: 13.0

Issue date: 25/07/2025

Supersedes: 17/08/2022

FUELS, DIESEL

SECTION 7: Handling and storage

Precautions for safe handling

Precautions for safe handling

: Provide adequate ventilation. Do not breathe vapours. Avoid contact with skin, eyes and clothing. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Take any precaution to avoid mixing with Incompatible materials, Refer to Section 10 on Incompatible Materials. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Avoid release to the environment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Product may release Hydrogen Sulphide: A specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to

help determine controls appropriate to local circumstances.

Hygiene measures

: Keep good industrial hygiene. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage conditions

: Storage of flammable liquids. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Do not store near or with any of the incompatible materials listed in section 10. Bund storage facilities to prevent soil and water pollution in the event of spillage. Take precautionary measures against static discharge.

Incompatible materials Heat and ignition sources : Oxidising agents. Strong acids. Bases.

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

Special rules on packaging

: Containers which are opened should be properly resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Packaging materials

: Keep only in the original container. Suitable material: Mild steel, Stainless steel.

Germany

German storage class (LGK) : LGK 3 - Flammable liquids

Switzerland

Storage class (LK) : LK 3 - Flammable liquids

Specific end use(s)

see attached exposure scenario.



Page: 7 / 22

Revision nr : 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Fuels, diesel (68334-30-5)			
Belgium - Occupational Exposure Limits			
Local name	Gazole (vapeur et aérosol) en hydrocarbures totales # Dieselbrandstof, (damp en aërosol) als totale koolwaterstoffen		
OEL TWA	100 mg/m³ (aerosol and vapor)		
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.		
OEL chemical category	Skin		
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023		
Ireland - Occupational Exposure Limits			
OEL TWA	100 mg/m³		
OEL STEL	300 mg/m³ (calculated)		
Portugal - Occupational Exposure Limits			
Local name	Fuel diesel, expresso como hidrocarbonetos totais		
OEL TWA	100 mg/m³ (inhalable fraction; vapor (Diesel fuel)		
OEL chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans as total hydrocarbons, skin - potential for cutaneous exposure		
Remark	P (Toxicidade percutânea); A3 (Agente carcinogénico confirmado nos animais de laboratorio con relevância desconhecida no Homem)		
Regulatory reference	Norma Portuguesa NP 1796:2014		
USA - ACGIH - Occupational Exposure Limits	USA - ACGIH - Occupational Exposure Limits		
Local name	Diesel oil, as total hydrocarbons		
ACGIH® TLV® TWA	100 mg/m³ (inhalable fraction and vapor)		
Remark (ACGIH)	TLV® Basis: Dermatitis. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)		
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans, Skin - potential significant contribution to overall exposure by the cutaneous route		
Regulatory reference	ACGIH 2024		



Page: 8 / 22

Revision nr: 13.0

Issue date: 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

8.1.2. Recommended monitoring procedures

Monitoring methods	
_	Concentration measurement in air. Personal air monitoring. Personal air monitoring. Room air monitoring.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

FUELS, DIESEL (68334-30-5)		
DNEL/DMEL (workers)		
Acute - systemic effects, inhalation	4288 mg/m ³	
Long-term - systemic effects, dermal	2,91 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	68,34 mg/m³	
DNEL/DMEL (general population)		
Acute - systemic effects, inhalation	2572,8 mg/kg bodyweight/day	
Long-term - systemic effects,oral	1,25 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	20,22 mg/m³	
Long-term - systemic effects, dermal	1,25 mg/kg bodyweight/day	

Additional information

: Recommended monitoring procedures :. Personal air monitoring. Room air monitoring

8.1.5. Control banding

No additional information available

8.2. Exposure controls

Engineering measure(s)

: Provide adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Organisational measures to prevent/limit releases, dispersion and exposure. See Section 7 for information on safe handling. Take precautionary measures against static discharges. Ensure equipment is adequately earthed. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Personal protective equipment

 The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.



Page: 9 / 22

Revision nr: 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Hand protection : Wear chemically resistant gloves (tested to EN374) . Suitable material: NBR

(Nitrile rubber). Breakthrough time: refer to the recommendations of the supplier. Thickness of the glove material: Not determined. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Eye protection : Use suitable eye protection (EN166): Safety glasses

Body protection : Wear suitable protective clothing

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Half-

face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: A (EN 14387). The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be

used. (EN 137)

Thermal hazard protection : Not required for normal conditions of use. Use dedicated equipment.

Environmental exposure controls : Do not allow to enter into surface water or drains. Comply with applicable

Community environmental protection legislation. Avoid release to the

environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : No data available.

Appearance : Liquid.

Odour : Characteristic.
Odour threshold : No data available

Melting / freezing point : -40 - 6 °C Freezing point : Not available Initial boiling point and boiling range : 141 - 462 °C

Flammability : Flammable liquid and vapour.

Explosive properties : Not applicable. The study does not need to be conducted because there are

no chemical groups associated with explosive properties present in the

molecule.

: 3,9 - 6

Oxidising properties : Not applicable. The classification procedure needs not to be applied because

there are no chemical groups present in the molecule which are associated

with oxidising properties.

Lower explosion limit: 0,6 vol %Upper explosion limit: 6,5 vol %Flash point: > 56 °CAuto-ignition temperature: ≥ 225 °C

Decomposition temperature : No data available pH : Not applicable

Kinematic viscosity : ≥ 1,5 mm²/s

Dynamic viscosity : No data availab

Dynamic viscosity : No data available Solubility : Water: < 20 mg/l

Partition coefficient n-octanol/water (Log

Kow)

Vapour pressure : 0,4 kPa



Page: 10 / 22

Revision nr: 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Vapour pressure at 50°C : Not available

Density : Not available

Relative density : 0,8 – 0,91 g/cm³

Vapour density : No data available

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour. Reference to other sections: 10.4 & 10.5.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Avoid the build-up of electrostatic charge. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. See Section 7 for information on safe handling.

10.5. Incompatible materials

Oxidising agents. Strong acids. Bases. See Section 7 for information on safe handling.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO2). Sulphur oxides. Hydrogen sulfide. Sulphuric acid. Reference to other sections 5.2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not

met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not

met)

Acute toxicity (inhalation) : Harmful if inhaled.

Fuels, diesel (68334-30-5)	
LD50/oral/rat	> 5000 mg/kg bodyweight (OECD 401)
LD50/dermal/rabbit	> 2000 mg/kg (Source: NLM_CIP)
LC50/inhalation/4h/rat	4,1 mg/l (OECD 403)



Page: 11 / 22

Revision nr: 13.0

Issue date: 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Skin corrosion/irritation Causes skin irritation.

pH: Not applicable

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not

pH: Not applicable

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not

met)

Carcinogenicity : Suspected of causing cancer.

Fuels, diesel (68334-30-5)		
IARC group	2B - Possibly carcinogenic to humans	
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)	
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)	
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.	

Fuels, diesel (68334-30-5)	
NOAEL (dermal, rat/rabbit, 90 days)	30 mg/kg bodyweight/day
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : May be fatal if swallowed and enters airways.

FUELS, DIESEL (68334-30-5)	
Kinematic viscosity	≥ 1,5 mm²/s

Fuels, diesel (68334-30-5)	
Kinematic viscosity	≥ 1,5 mm²/s
Hydrocarbon	Yes

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

11.2.2. Other information

Other information : Symptoms related to the physical, chemical and toxicological

characteristics, For further information see section 4

SECTION 12: Ecological information



Page: 12 / 22

Revision nr : 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes : 17/08/2022

12.1. Toxicity

Environmental properties : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment,

short-term (acute)

: Not classified

Hazardous to the aquatic environment,

long-term (chronic)

: Toxic to aquatic life with long lasting effects.

Fuels, diesel (68334-30-5)	
LC50 - Fish [1]	21 mg/l Oncorhynchus mykiss (Rainbow trout)
LC50 - Other aquatic organisms [1]	> 1000 mg/l (40 hours)
EC50 - Crustacea [1]	68 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	22 mg/l Raphidocelis subcapitata
NOEC chronic fish	0,083 mg/l Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0,2 mg/l Daphnia magna (Water flea)

12.2. Persistence and degradability

FUELS, DIESEL (68334-30-5)	
Persistence and degradability	Readily biodegradable.

Fuels, diesel (68334-30-5)	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

FUELS, DIESEL (68334-30-5)	
Partition coefficient n-octanol/water (Log Kow)	3,9 – 6
Bioaccumulative potential	No additional information available.

Fuels, diesel (68334-30-5)	
Partition coefficient n-octanol/water	study scientifically unjustified

12.4. Mobility in soil

FUELS, DIESEL (68334-30-5)			
Mobility in soil No data available			
Ecology - soil	No data available.		

Fuels, diesel (68334-30-5)	
Surface tension	not relevant



Page: 13 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

12.5. Results of PBT and vPvB assessment

FUELS, DIESEL (68334-30-5)	
Results of PBT assessment	Not applicable

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Avoid release to the environment. Dispose of empty containers and wastes safely. See Section 7 for information on safe handling. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Packaging contaminated by the product: Do not pierce or burn, even after use. Never use pressure to empty container.

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC)

This material and its container must be disposed of as hazardous waste Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities

The following Waste Codes are only suggestions:

13 07 01* - fuel oil and diesel

15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number or	ID number			
1202	1202	1202	1202	1202
14.2. UN proper ship	ping name			
DIESEL FUEL	DIESEL FUEL	Diesel fuel	DIESEL FUEL	DIESEL FUEL
Transport document de	scription			
UN 1202 DIESEL FUEL, 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, MARINE POLLUTANT/ENVIRO NMENTALLY HAZARDOUS	UN 1202 Diesel fuel, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS	UN 1202 DIESEL FUEL, 3, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
3	3	3	3	3



Page: 14/22

Revision nr: 13.0

Issue date: 25/07/2025

Supersedes: 17/08/2022

FUELS, DIESEL

ADR	IMDG	IATA	ADN	RID
1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1	3	1 1 1 1 1 1 1 1 1 1	3
14.4. Packing group				
III	III	III	III	III
14.5. Environmental	<u>hazards</u>			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
		ADN :N2		

Special precautions for user

Special precautions for user : No data available

- Overland transport

Classification code (ADR) F1

Special provisions 640K, 664

51 Limited quantities (ADR) Excepted quantities (ADR) E1

P001, IBC03, LP01, R001 Packing instructions (ADR)

Mixed packing provisions (ADR) **MP19** Portable tank and bulk container T2

instructions (ADR)

Portable tank and bulk container

special provisions (ADR)

TP1

Tank code (ADR) **LGBF** Vehicle for tank carriage FL Transport category (ADR) 3 Special provisions for carriage -V12

Packages (ADR)

Special provisions for carriage -

Operation (ADR)

S2

Hazard identification number (Kemler:

No.)

Orange plates

30

1202

30

Tunnel restriction code D/E EAC code 3Y

- Transport by sea

Special provisions (IMDG) : 363 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1

Packing instructions (IMDG) : P001, LP01 IBC packing instructions (IMDG) : IBC03 Tank instructions (IMDG) : T2



Page: 15 / 22

Revision nr: 13.0

Issue date: 25/07/2025

Supersedes: 17/08/2022

FUELS, DIESEL

: TP1 Tank special provisions (IMDG) EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E Stowage category (IMDG) : A

Properties and observations (IMDG) : Immiscible with water.

- Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y344 PCA limited quantity max net quantity : 10L

(IATA)

PCA packing instructions (IATA) : 355 PCA max net quantity (IATA) : 60L : 366 CAO packing instructions (IATA) CAO max net quantity (IATA) : 220L Special provisions (IATA) : A3 ERG code (IATA) : 3L

- Inland waterway transport

: F1 Classification code (ADN) Special provisions (ADN) : 640K Limited quantities (ADN) : 5 L Excepted quantities (ADN) : E1 : T Carriage permitted (ADN)

: PP, EX, A Equipment required (ADN) Ventilation (ADN) : VE01 Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : F1 : 640K Special provisions (RID) Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19 Portable tank and bulk container : T2

instructions (RID)

Portable tank and bulk container special: TP1

provisions (RID)

Tank codes for RID tanks (RID) : LGBF Transport category (RID) : 3 Special provisions for carriage -: W12

Packages (RID)

: CE4 Colis express (express parcels) (RID) Hazard identification number (RID) : 30

14.7. Maritime transport in bulk according to IMO instruments

Code: IBC : No data available.



Page: 16 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	FUELS, DIESEL; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	FUELS, DIESEL; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	FUELS, DIESEL; Fuels, diesel	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	FUELS, DIESEL; Fuels, diesel	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)



Page: 17 / 22

Revision nr: 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes : 17/08/2022

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Detergent Regulation (648/2004/EC): Labelling of contents

Labelling for contents according to regulation (EC) No. 648/2004

: Not applicable

15.1.2. National regulations



Page: 18 / 22

Revision nr: 13.0

Issue date: 25/07/2025

Supersedes: 17/08/2022

FUELS, DIESEL

France

Installations classées				
No ICPE	Désignation de la rubrique	Code Régime	Rayon	
4734.text	Produits pétroliers spécifiques et carburants de substitution : essences et naphtas ; kérosènes (carburants d'aviation compris) ; gazoles (gazole diesel, gazole de chauffage domestique et mélanges de gazoles compris) ; fioul lourd ; carburants de substitution pour véhicules, utilisés aux mêmes fins et aux mêmes usages et présentant des propriétés similaires en matière d'inflammabilité et de danger pour l'environnement. La quantité totale susceptible d'être présente dans les installations y compris dans les cavités souterraines étant :			
4734.1a	1. Pour les cavités souterraines et les stockages enterrés : a) Supérieure ou égale à 2 500 t Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	A		
4734.1b	1. Pour les cavités souterraines et les stockages enterrés : b) Supérieure ou égale à 1 000 t mais inférieure à 2 500 t Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	Е	2	
4734.1c	1. Pour les cavités souterraines et les stockages enterrés : c) Supérieure ou égale à 50 t d'essence ou 250 t au total, mais inférieure à 1 000 t au total Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	DC	2	
4734.2a	2. Pour les autres stockages : a) Supérieure ou égale à 1 000 t Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	A	2	
4734.2b	2. Pour les autres stockages : b) Supérieure ou égale à 100 t d'essence ou 500 t au total, mais inférieure à 1 000 t au total Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	Е	2	
4734.2c	2. Pour les autres stockages : c) Supérieure ou égale à 50 t au total, mais inférieure à 100 t d'essence et inférieure à 500 t au total Quantité seuil bas au sens de l'article R. 511-10 : 2 500 t. Quantité seuil haut au sens de l'article R. 511-10 : 25 000 t.	DC	2	

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV;

ID No. 76).

Major Accidents Ordinance (12. BlmSchV) : Listed in the 12. BlmSchV (Annex I) under: 2.3.3

- Quantity threshold for operational area under § 1 para. 1

- Sentence 1 :2500000 kg - Sentence 2 :25000000 kg



Page: 19 / 22

Revision nr: 13.0

Issue date : 25/07/2025

FUELS, DIESEL

Supersedes: 17/08/2022

Netherlands

Waterbezwaarlijkheid : categorie Z(2) - afbreekbare stoffen met gevaarlijke eigenschappen voor

mens en milieu (carcinogeniteit/ mutageniteit/

reprotoxiciteit/bioacumulerend vermogen of toxiciteit)

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

SZW-lijst van reprotoxische stoffen -

Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen -

Ontwikkeling

: FUELS, DIESEL is listed: The substance is not listed: The substance is not listed

: The substance is not listed

: The substance is not listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids

must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in

direct contact with the product

The requirements from the Danish Working Environment Authorities

regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

1.3	Details of the supplier of the safety data sheet	Modified	
2.2	Precautionary statements (CLP)	Update	
3	Composition/informat ion on ingredients	Modified	
16	Other information	Modified	

Abbreviations and acronyms:

ABM = Algemene beoordelingsmethodiek	
ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin	
ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route	
CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC	
IATA = International Air Transport Association	
IMDG = International Maritime Dangerous Goods Code	
LEL = Lower Explosive Limit/Lower Explosion Limit	
UEL = Upper Explosion Limit/Upper Explosive Limit	
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals	
BTT = Breakthrough time (maximum wearing time)	
DMEL = Derived Minimal Effect level	
DNEL = Derived No Effect Level	
EC50 = Median Effective Concentration	
EL50 = Median effective level	
ErC50 = EC50 in terms of reduction of growth rate	
ErL50 = EL50 in terms of reduction of growth rate	
EWC = European waste catalogue	
LC50 = Median lethal concentration	



Page: 20 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

LD50 = Median lethal dose
LL50 = Median lethal level
NA = Not applicable
NOEC = No observed effect concentration
NOEL: no-observed-effect level
NOELR = No observed effect loading rate
NOAEC = No observed adverse effect concentration
NOAEL = No observed adverse effect level
N.O.S. = Not Otherwise Specified
OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
PNEC = Predicted No Effect Concentration
Quantitative structure-activity relationship (QSAR)
STOT = Specific Target Organ Toxicity
TWA = time weighted average
VOC = Volatile organic compounds
WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet

Sources of key data used to compile the : ECHA (European Chemicals Agency). LOLI Database. Supplier information.

Training advice

: Training staff on good practice. Manipulations are to be done only by qualified

and authorised persons.

Other information

: Hazard classification and labeling of petroleum substances in the European

Economic Area, Concawe – 2025 (http://www.concawe.eu).

Full text of H- and EUH-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
Carc. 2	Carcinogenicity, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H332	Harmful if inhaled.	
H351	Suspected of causing cancer.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	

Full text of use descriptors

ERC2	Formulation into mixture	
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	
ERC5	Use at industrial site leading to inclusion into/onto article	
ERC6a	Use of intermediate	
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)	
ERC6c	Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)	



Page: 21 / 22

Revision nr: 13.0

Issue date : 25/07/2025

Supersedes : 17/08/2022

FUELS, DIESEL

ERC6d	Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)	
ERC7	Use of functional fluid at industrial site	
ERC9a	Widespread use of functional fluid (indoor)	
ERC9b	Widespread use of functional fluid (outdoor)	
ESVOC SPERC 1.1b.v1	Distribution: Industrial (SU3)	
ESVOC SPERC 2.2.v1	Formulation & packing of preparations and mixtures: Industrial (SU10)	
ESVOC SPERC 6.1a.v1	Manufacture of substances: Industrial (SU8, SU9)	
ESVOC SPERC 7.12a.v1	Use as a fuel: Industrial (SU3)	
ESVOC SPERC 7.13a.v1	Functional fluids: Industrial (SU3)	
ESVOC SPERC 9.12b.v1	Use as a fuel: Professional (SU22)	
ESVOC SPERC 9.12c.v1	Use as a fuel: Consumer (SU21)	
PC13	Fuels	
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions	
PROC14	Tabletting, compression, extrusion, pelettisation, granulation	
PROC15	Use as laboratory reagent	
PROC16	Use of fuels	
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions	
PROC28	Manual maintenance (cleaning and repair) of machinery	
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition	
PROC4	Chemical production where opportunity for exposure arises	
PROC5	Mixing or blending in batch processes	
PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities	
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities	
PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	
QUALITATIVE ASSESSMENT FOR ENVIRONMENT		
SU8	Manufacture of bulk, large scale chemicals (including petroleum products)	
SU9	Manufacture of fine chemicals	

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Classification according to Regulation (EC) No. 1272/2008 [CLP] Labelling according to Regulation (EC) No. 1272/2008 [CLP]

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS



information may not be applicable.